



## SLOTING CUTTER ONLY

Replacement and additional cutters can be purchased singularly for economy where you have an existing arbor.

**NEW**




CARBIDE TIPPED - TWO FLUTES  
CUTTER BORE 8mm (5/16")

PART No.	A		B	
	in.	mm	in.	mm
T 500-1.6 M	2	50.8	1/16	1.6
T 500-2 M	2	50.8	5/64	2
T 500-2.5 M	2	50.8	3/32	2.5
T 500-2.8 M	2	50.8	7/64	2.8
T 500-3.2 M	2	50.8	1/8	3.2
T 500-3.6 M	2	50.8	9/64	3.6
T 500-4 M	2	50.8	5/32	4
T 500-4.8 M	2	50.8	3/16	4.8
T 500-5.5 M	2	50.8	7/32	5.5
T 500-6.4 M	2	50.8	1/4	6.35
T 500-8.0 M	2	50.8	5/16	8

## ASSEMBLIES

By using the guide on your routing machine, the maximum depth of cut can be obtained.

**NEW**




CARBIDE TIPPED - TWO FLUTES  
SUFFIX 1/2 = 1/2" SHANK, OTHERWISE 1/4"

PART No.	B		ARBOR
	in.	mm	
TA 500-1.6 M	1/16	1.6	TA 15
TA 500-1.6 M 1/2	1/16	1.6	TA 16
TA 500-2 M	5/64	2	TA 15
TA 500-2 M 1/2	5/64	2	TA 16
TA 500-2.5 M	3/32	2.5	TA 15
TA 500-2.5 M 1/2	3/32	2.5	TA 16
TA 500-2.8 M	7/64	2.8	TA 15
TA 500-2.8 M 1/2	7/64	2.8	TA 16
TA 500-3.2 M	1/8	3.2	TA 15
TA 500-3.2 M 1/2	1/8	3.2	TA 16
TA 500-3.6 M	9/64	3.6	TA 15
TA 500-3.6 M 1/2	9/64	3.6	TA 16
TA 500-4 M	5/32	4	TA 15
TA 500-4 M 1/2	5/32	4	TA 16
TA 500-4.8 M	3/16	4.8	TA 15
TA 500-4.8 M 1/2	3/16	4.8	TA 16
TA 500-5.5 M	7/32	5.5	TA 15
TA 500-5.5 M 1/2	7/32	5.5	TA 16
TA 500-6.4 M	1/4	6.4	TA 15
TA 500-6.4 M 1/2	1/4	6.4	TA 16
TA 500-8.0 M	5/16	8	TA 15
TA 500-8.0 M 1/2	5/16	8	TA 16

## ASSEMBLIES

Ball bearing guide eliminates the cumbersome and time consuming job of setting up router machine guides.

**NEW**



CARBIDE TIPPED - TWO FLUTES  
WITH BALL BEARING GUIDE  
SUFFIX 1/2 = 1/2" SHANK, OTHERWISE 1/4"


PART No.	B		ARBOR
	in.	mm	
TA 500-1.6 MB	1/16	1.6	TA 4
TA 500-1.6 MB 1/2	1/16	1.6	TA 5
TA 500-2 MB	5/64	2	TA 4
TA 500-2 MB 1/2	5/64	2	TA 5
TA 500-2.5 MB	3/32	2.5	TA 4
TA 500-2.5 MB 1/2	3/32	2.5	TA 5
TA 500-2.8 MB	7/64	2.8	TA 4
TA 500-2.8 MB 1/2	7/64	2.8	TA 5
TA 500-3.2 MB	1/8	3.2	TA 4
TA 500-3.2 MB 1/2	1/8	3.2	TA 5
TA 500-3.6 MB	9/64	3.6	TA 4
TA 500-3.6 MB 1/2	9/64	3.6	TA 5
TA 500-4 MB	5/32	4	TA 4
TA 500-4 MB 1/2	5/32	4	TA 5
TA 500-4.8 MB	3/16	4.8	TA 4
TA 500-4.8 MB 1/2	3/16	4.8	TA 5
TA 500-5.5 MB	7/32	5.5	TA 4
TA 500-5.5 MB 1/2	7/32	5.5	TA 5
TA 500-6.4 MB	1/4	6.4	TA 4
TA 500-6.4 MB 1/2	1/4	6.4	TA 5
TA 500-8.0 MB	5/16	8	TA 1
TA 500-8.0 MB 1/2	5/16	8	TA 3

Replacement Ball Bearing TB12.

## SLOTING CUTTER ONLY

Four flute cutters are used for extra smooth cutting and smoother finishes with longer tool life between sharpenings.

**NEW**




CARBIDE TIPPED - FOUR FLUTES  
CUTTER BORE 8 mm (5/16")  
TX SERIES: BORE 12.7 mm (1/2")

PART No.	A		B	
	in.	mm	in.	mm
T 700-1.6 M	2	50.8	1/16	1.6
T 700-2 M	2	50.8	5/64	2
T 700-2.5 M	2	50.8	3/32	2.5
T 700-2.8 M	2	50.8	7/64	2.8
T 700-3.2 M	2	50.8	1/8	3.2
T 700-3.6 M	2	50.8	9/64	3.6
T 700-4 M	2	50.8	5/32	4
T 700-4.8 M	2	50.8	3/16	4.8
T 700-5.5 M	2	50.8	7/32	5.5
T 700-6.4 M	2	50.8	1/4	6.35
T 700-8.0 M	2	50.8	5/16	8
TX 700-4.8 M	3-5/32	80	3/16	4.8
TX 700-5.5 M	3-5/32	80	7/32	5.5
TX 700-6.4 M	3-5/32	80	1/4	6.35
TX 700-8 M	3-5/32	80	5/16	8

## ASSEMBLIES

Bits without bearings can be used where the bearing and nut interfere with the work piece configuration.

**NEW**




CARBIDE TIPPED - FOUR FLUTES  
TX CUTTERS: MAX DEPTH 30mm WIDTH 80mm.  
SUFFIX 1/2 = 1/2" SHANK, OTHERWISE 1/4"

PART No.	B		ARBOR
	in.	mm	
TA 700-1.6 M	1/16	1.6	TA 15
TA 700-1.6 M 1/2	1/16	1.6	TA 16
TA 700-2 M	5/64	2	TA 15
TA 700-2 M 1/2	5/64	2	TA 16
TA 700-2.5 M	3/32	2.5	TA 15
TA 700-2.5 M 1/2	3/32	2.5	TA 16
TA 700-2.8 M	7/64	2.8	TA 15
TA 700-2.8 M 1/2	7/64	2.8	TA 16
TA 700-3.2 M	1/8	3.2	TA 15
TA 700-3.2 M 1/2	1/8	3.2	TA 16
TA 700-3.6 M	9/64	3.6	TA 15
TA 700-3.6 M 1/2	9/64	3.6	TA 16
TA 700-4 M	5/32	4	TA 15
TA 700-4 M 1/2	5/32	4	TA 16
TA 700-4.8 M	3/16	4.8	TA 15
TA 700-4.8 M 1/2	3/16	4.8	TA 16
TXA 700-4.8 M 1/2	3/16	4.8	TA 8
TA 700-5.5 M	7/32	5.5	TA 15
TA 700-5.5 M 1/2	7/32	5.5	TA 16
TXA 700-5.5 M 1/2	7/32	5.5	TA 8
TA 700-6.4 M	1/4	6.4	TA 15
TA 700-6.4 M 1/2	1/4	6.4	TA 16
TXA 700-6.4 M 1/2	1/4	6.4	TA 8
TA 700-8 M	5/16	8	TA 15
TA 700-8 M 1/2	5/16	8	TA 16
TXA 700-8 M 1/2	5/16	8	TA 8

## ASSEMBLIES

Four flute bits with ball bearing guide produce an accurate and professional job with minimum set up time.

**NEW**



CARBIDE TIPPED - FOUR FLUTES  
WITH BALL BEARING GUIDE  
TX CUTTERS: MAX DEPTH 29mm WIDTH 80mm.  
SUFFIX 1/2 = 1/2" SHANK, OTHERWISE 1/4"

PART No.	B		ARBOR
	in.	mm	
TA 700-1.6 MB	1/16	1.6	TA 4
TA 700-1.6 MB 1/2	1/16	1.6	TA 5
TA 700-2 MB	5/64	2	TA 4
TA 700-2 MB 1/2	5/64	2	TA 5
TA 700-2.5 MB	3/32	2.5	TA 4
TA 700-2.5 MB 1/2	3/32	2.5	TA 5
TA 700-2.8 MB	7/64	2.8	TA 4
TA 700-2.8 MB 1/2	7/64	2.8	TA 5
TA 700-3.2 MB	1/8	3.2	TA 4
TA 700-3.2 MB 1/2	1/8	3.2	TA 5
TA 700-3.6 MB	9/64	3.6	TA 4
TA 700-3.6 MB 1/2	9/64	3.6	TA 5
TA 700-4 MB	5/32	4	TA 4
TA 700-4 MB 1/2	5/32	4	TA 5
TA 700-4.8 MB	3/16	4.8	TA 4
TA 700-4.8 MB 1/2	3/16	4.8	TA 5
TXA 700-4.8 MB 1/2	3/16	4.8	TA 7
TA 700-5.5 MB	7/32	5.5	TA 4
TA 700-5.5 MB 1/2	7/32	5.5	TA 5
TXA 700-5.5 MB 1/2	7/32	5.5	TA 7
TA 700-6.4 MB	1/4	6.4	TA 4
TA 700-6.4 MB 1/2	1/4	6.4	TA 5
TXA 700-6.4 MB 1/2	1/4	6.4	TA 7
TA 700-8 MB	5/16	8	TA 1
TA 700-8 MB 1/2	5/16	8	TA 3
TXA 700-8 MB 1/2	5/16	8	TA 7

Replacement Ball Bearing TB12.

